

01 • GOOSENECK MICROPHONE

Pluggable Gooseneck Microphone

Screw-lock removable gooseneck with a two-color LED ring and anti-wind foam — available in five lengths from 220 mm to 600 mm.

A precise mini directional condenser capsule that plugs into the DIALOGUE discussion units through a Mini 6-pin screw-lock socket. The two-color LED ring shows speaking (red) and request-to-speak / awaiting-chairman (green), while strong audio pickup and immunity to GSM / mobile interference keep speech clear across every gooseneck length. Choose the length that suits chairman and delegate positions — the electrical performance is identical across the range.



BR-DCU-G series — supplied in 600 / 485 / 410 / 330 / 220 mm lengths, each with an anti-wind foam cover.

HEADLINE CAPABILITIES

- Two-color LED ring — red = speaking, green = awaiting chairman
- Precise mini directional (cardioid) head
- Screw-lock socket for removable microphone
- Anti-wind foam cover
- Immune to GSM / mobile interference
- Five lengths, identical audio performance

01.1 Features & Functions

CAPSULE · INDICATION

- **Precise directional head** with a mini design for strong, focused pickup.
- **Two-color LED ring** indicator — red for speaking, green when awaiting the chairman's acceptance to speak.
- **Anti-wind foam cover** supplied.
- Strong audio collection across all gooseneck lengths.
- Immune to GSM / mobile-phone interference.
- **Screw-lock socket** to connect a removable microphone to the discussion unit.

01.2 Technical Parameters

COMMON TO ALL MODELS

Directivity	Cardioid	Microphone type	Condenser
Sensitivity	-46 dBV/Pa	Maximum SPL	125 dB (THD < 3%)
Frequency response	30 Hz – 20 kHz	Input impedance	2 kΩ
Equivalent noise	20 dBA (SPL)	Connection	Mini 6-pin (screw-lock)
Signal-to-noise ratio	≥ 96 dB	Colour	Black
Working temp.	0 °C ~ 45 °C	Storage temp.	-20 °C ~ 50 °C

01.3 Model Comparison

LENGTH · WEIGHT

Model	BR-DCU-G600	BR-DCU-G485	BR-DCU-G410	BR-DCU-G330	BR-DCU-G220
Length	600 mm	485 mm	410 mm	330 mm	220 mm
Weight	88.5 g	78 g	72 g	62 g	58 g
Anti-wind foam	Yes	Yes	Yes	Yes	Yes

01.4 Ordering Information

MODEL FOR ORDER

Order code	Description
BR-DCU-G600	600 mm pluggable gooseneck microphone, with anti-wind foam cover
BR-DCU-G485	485 mm pluggable gooseneck microphone, with anti-wind foam cover
BR-DCU-G410	410 mm pluggable gooseneck microphone, with anti-wind foam cover
BR-DCU-G330	330 mm pluggable gooseneck microphone, with anti-wind foam cover
BR-DCU-G220	220 mm pluggable gooseneck microphone, unique design



Engineered for Indian boardrooms, ministries, courtrooms and broadcast halls — the wired DIALOGUE conference series.

ABOUT BRONX SYSTEMS

An Indian Original Equipment Manufacturer. ISO certified · MSME · Make in India · NSIC. Bronx Systems supplies professional audio-visual, conference, control-room and signage solutions to government, defence, broadcast and enterprise customers across India.

SALES

sales@bronx.co.in

WEB

www.bronx.co.in

DOCUMENT

BR-DCU-G Series
Datasheet · 2026

REVISION

Rev. A · 3 pages